



# HT 365™ Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Date of issue: 03/13/2017 Revision date: N/A Supersedes: N/A Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : HT 365™  
Product form : Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Rust and corrosion inhibitor. Water-displacing agent. Lubricant. Penetrating fluid. Shake well before use.

### 1.3. Details of the supplier of the safety data sheet

HoldTight Solutions Inc.  
P.O. Box 27907  
Houston, TX 77227-7907  
713-266-9339/800-319-8802  
www.holdtight.com

### 1.4. Emergency telephone number

Emergency number : Hazmat Service 1-800-373-7542 (Contract #: 1190)



## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture


#### Classification (GHS-US)

Flam. Liq. 3 H226  
Asp. Tox. 1 H304

### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof ventilating, lighting, electrical equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P280 - Wear eye protection, face shield, protective gloves, protective clothing  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER  
P303 + P361 + P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P331 - Do NOT induce vomiting  
P370 + P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish  
P403 + P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to licensed waste handling facility

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	30 - 60

**SECTION 4: First aid measures****4.1. Description of first aid measures**

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : IF ON SKIN (or clothing), remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation persists, call a physician.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : IF SWALLOWED: Immediately give large amounts of water. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

**4.2. Most important symptoms and effects, both acute and delayed**

- Symptoms/injuries : May be fatal if swallowed and enters airways.
- Symptoms/injuries after inhalation : Respiratory effects of acute exposure include irritation of the nose and throat, coughing, sneezing, reflex bronchospasm, dyspnea and pulmonary edema.
- Symptoms/injuries after skin contact : May cause skin irritation.
- Symptoms/injuries after eye contact : May cause slight irritation.
- Symptoms/injuries after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

**4.3. Indication of any immediate medical attention and special treatment needed**

No additional information available

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.
- Unsuitable extinguishing media : Water.

**5.2. Special hazards arising from the substance or mixture**

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known under normal conditions of use.

**5.3. Advice for firefighters**

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- General measures : Remove ignition sources. Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

**6.1.1. For non-emergency personnel**

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

**6.1.2. For emergency responders**

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

**6.2. Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

# HT 365™

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe vapors and mists. Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

### 8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas.  
Personal protective equipment : Gloves. Protective goggles. High gas/vapor concentration: gas mask.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.  
Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.  
Skin and body protection : Wear suitable protective clothing. Wear long sleeves.  
Respiratory protection : Where excessive vapor, mist, or dust may result, use NIOSH approved respiratory protection equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Brown-yellow.  
Odor : Characteristic.  
Odor Threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : <-5 °C  
Freezing point : No data available  
Boiling point : 160 - >300 °C  
Flash point : 50 °C (122°F)(Open cup)  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : 0.28 psi (Reid Method, ASTM D 323)  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Density : 0.83 g/ml  
Solubility : Insoluble in water.  
Log Pow : No data available

# HT 365™

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Kow : No data available  
Viscosity, kinematic : 6.02 cSt (at 40°C, ASTM D445.a); 2.05 cSt (at 100°C, ASTM D445.a)  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosive limits : 0.6 - 8 vol %

### 9.2. Other information

VOC content : 38 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Sulfur oxides. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : Respiratory effects of acute exposure include irritation of the nose and throat, coughing, sneezing, reflex bronchospasm, dyspnea and pulmonary edema.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : May cause slight irritation.

Symptoms/injuries after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

# HT 365™

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- 12.3. **Bioaccumulative potential** : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- 12.4. **Mobility in soil** : No additional information available
- 12.5. **Other adverse effects** : No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : Exempted from Hazmat (49CFR 173.150 (F)) in non-bulk packaging.
- Bulk Description : UN1993 Flammable liquids, n.o.s., (contains Petroleum Distillates) 3, III
- UN-No.(DOT) : 1993
- DOT NA no. : UN1993
- DOT Proper Shipping Name : Flammable liquids, n.o.s. (contains Petroleum Distillates)
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### Additional information

- Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

HT 365™	
All chemical substances in this product are listed in the EPA (Environmental Protection Agency) TSCA (Toxic Substances Control Act) Inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard

#### 15.2. International regulations

##### CANADA

No additional information available

#### 15.3. US State regulations

##### California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# HT 365™

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

U.S. - Massachusetts - Right To Know List


### Distillates, petroleum, solvent-dewaxed light paraffinic (64742-56-9)

U.S. - Massachusetts - Right To Know List

## SECTION 16: Other information

Indication of changes : Version 1.0: New SDS Created  
Revision date : N/A  
Other information : Author: TA.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.  
NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2  
Flammability : 2  
Physical : 0  
Personal Protection :

To the best of our knowledge, the information contained herein is accurate. However, HoldTight Solutions Inc. nor any of its distributors assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.